



Specifications Sylvania LED Downlight  
Start 150 Aluminium White 12W  
1200lm 77D - 830 Warm White |  
Cutout 150mm - IP54

[View Product](#)

## General Information

|                          |                            |
|--------------------------|----------------------------|
| SKU                      | 255256                     |
| EAN                      | 5410288303246              |
| Brand                    | Sylvania                   |
| Manufacturer Name        | ST DWNLT 150 IP54 1200 830 |
| Any Lamp all-in warranty | 5 Years                    |
| Average Lifetime (h)     | 100000                     |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tilttable                   | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 1x18              |
| Wattage                     | 12                |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |

|                          |                                    |
|--------------------------|------------------------------------|
| Beam Angle (degree)      | 77                                 |
| Luminous Flux (Lumen)    | 1200                               |
| Luminous Efficacy (lm/W) | 100                                |
| Power factor             | >0.90                              |
| Unified Glare Rating     | < 25 - for hallways and staircases |
| Optical Cover            | Opal                               |
| Product Type Category    | LED Downlight                      |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| IP-rating              | IP54                   |
| Impact Protection (IK) | IK07 - 2 joules        |
| Operating Temperature  | -10 to +40             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 45  |
| Diameter (mm) | 165 |

## Sensor Information

|                |                                   |
|----------------|-----------------------------------|
| Type of sensor | <b>Why Any-lamp?</b><br>No Sensor |
|----------------|-----------------------------------|

💡 Order from the **largest lighting specialist** in Europe 📄 **Customised** quotation

🏆 Up to **7 years warranty** ↩️ **Easy** return process