



Specifications Noxion LED Downlight Slim V2.0 12W 1200lm 120D - 840 Cool White | 170mm - IP44 - Emergency 3H

[View Product](#)

General Information

|                          |                                                                                   |
|--------------------------|-----------------------------------------------------------------------------------|
| SKU                      | 238917                                                                            |
| EAN                      | 8719157015066                                                                     |
| Brand                    | Noxion                                                                            |
| Manufacturer Name        | Noxion LED Downlight Slim V2.0 IP44 12W 4000K Cutout Ø150mm Frame Ø170mm w/ EM3HR |
| Any Lamp all-in warranty | 6 Years                                                                           |
| Average Lifetime (h)     | 50000                                                                             |

Technical Information

|                             |                     |
|-----------------------------|---------------------|
| Emergency Lighting          | With Emergency Unit |
| Tiltable                    | No                  |
| Technology                  | LED Integrated      |
| Wattage                     | 12                  |
| Voltage (V)                 | 220-240             |
| Dimmable                    | Not Dimmable        |
| Colour Code                 | 840 Cool White      |
| Colour temperature (Kelvin) | 4000 Cool White     |
| Colour Rendering (Ra)       | 80-89               |
| Colour of Light             | White               |
| Light colour options        | Single Color        |
| Driver Included             | Yes                 |

|                          |                                       |
|--------------------------|---------------------------------------|
| Beam Angle (degree)      | 120                                   |
| Luminous Flux (Lumen)    | 1200                                  |
| Luminous Efficacy (lm/W) | 100                                   |
| Power factor             | >0.90                                 |
| Installation Depth (mm)  | 19                                    |
| Unified Glare Rating     | < 28 - for hallways and storage rooms |
| Optical Cover            | PC (Polycarbonate)                    |
| Product Type Category    | LED Downlight                         |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 150               |
| IP-rating              | IP44              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature  | -20 to +40        |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Series                 | Slim              |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 26  |
| Diameter (mm) | 170 |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



**Up to 7 years warranty**

No Sensor



**Easy return process**